



- NOTES:**
1. PRESSURE: 10 - 150 PSI
 2. TEMP: -40 to +175°F
 3. MAT'L: BODY - ANODIZED ALUM.
SEAL - LOW TEMP BUNA
BALL - STAINLESS

FUNCTION:
SUPPLY AIR AT "1" PORT,
AIR FLOWS THRU THE "2"
PORTS. THE OPPOSITE "1"
PORT IS CLOSED.

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
ALKON CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
ALKON CORPORATION IS PROHIBITED.

DIMENSIONS ARE IN INCHES		NAME	DATE
TOLERANCES:		DRAWN	BM
FRACTIONAL ±.010		CHECKED	--
ANGULAR: MACH ±1/2°BEND ±		ENG APPR.	--
TWO PLACE DECIMAL ±.010		MFG APPR.	
THREE PLACE DECIMAL ±.005		Q.A.	
MATERIAL	--	FINISH	
RM. No.:	--		
DO NOT SCALE DRAWING			

ALKON CORPORATION
FREMONT, OHIO

1/4" SHUTTLE VALVE

SIZE	DWG. NO.	REV.
A	CD-SV-25	A
SCALE:1:1	WEIGHT: -	SHEET 1 OF 1